DEMINERALIZATORS MODEL ECODMS





Where it is necessary high qualità demineralisated water for any use of wahing, baths preparation and refilling.



APPLICATIONS

Surface Treatment Coating Anodic Oxidation Printed circuit boards ECOTEAM produces demineralisation plant with closed loop on rinsing systems and/or for the production of de-ionising water from raw water. The demineralisation process allows to eliminate

the pollutants dissolved in the water trough ionic exchange. The resins exchange cationic elements like Al³+, Ca²+, Mg²+, Ni²+, Na+, K+ with H+ and anionic elements like Cr⁶-, Cl-, NO³-, CN-, F- with OH-. lonic exchange is a reversible process. The regeneration is done using acid (HCl o $\rm H_2SO_4$) on cationic resin and base (NaOH) on anionic resin. Organic substances, that may pollute the ionic resins, are

treated with a granular carbon filter placed before the resin filters. Demineralisation plant can be produced in a single (Simplex) or double (Duplex) line. Simplex plant are designed for a maximum of two shifts otherwise Duplex plants are designed for 24/24 hours production. Demineralization plant are controlled via PLC in every processes phase.


ECOTEAM supplies the following options:


- pH and conductivity control in every phase.
- Regeneration of the single resin filter.
- Counter-current system.





MODELLO	HOUR PRODUTION [I/h]	SIMPLEX N° COLUMN	DUPLEX N° COLUMN
ECODMS-125	3.000	2 - 3 - 4	4 - 5 - 7
ECODMS-180	5.000	2 - 3 - 4	4 - 5 - 7
ECODMS-250	8.000	2 - 3 - 4	4 - 5 - 7
ECODMS-375	12.000	2 - 3 - 4	4 - 5 - 7
ECODMS-500	15.000	2 - 3 - 4	4 - 5 - 7
ECODMS-750	22.000	2 - 3 - 4	4 - 5 - 7
ECODMS-1000	30.000	2 - 3 - 4	4 - 5 - 7
ECODMS-2000	60.000	2 - 3 - 4	4 - 5 - 7


^(*) More details on demand














OPTIONS

Washing panel to clean the regeneration pipes
Double pump on alimentation
D.I. storage and pumping system
Acid and Base storages and control
Counter-current regeneration system
Regeneration of single column to reduce eluati
Mixed bed resins system for Ultra D.I. Water







